



RENOLIT DURAPLEX EP 00

Description;

RENOLIT DURAPLEX EP 00 is a freely grease based on Lithium complex soap for high demands on wear protection and pressure loading capacity.

RENOLIT DURAPLEX EP 00 stands out due to its good thermal stability, its very high drip point, its easy production and its excellent low – temperature flow behaviour.

Application;

RENOLIT DURAPLEX EP 00 is used in lubricating systems for the industry and for utility vehicles.

Characteristics;

Properties	Unit	Value	Testmethod
Designation	-	GP 00/000 N-40	DIN 51 502
Thickener	-	Lithium complex soap	
Service temperature range	°C	-40 to 140 and Company internal	DIN 51 805
Drop point	°C	Over 250	Method DIN ISO 2176
Behaviour to water	Assessment Stage	1-90	DIN 51-807-1
NLGI class	-	00/000	DIN 51 818
Working penetration	0.1 mm	420-450	DIN ISO 2137
Corrosion protection properties			
For steel (Emcor method)	Deg.corr.	0-0	DIN 51 802
Corrosion effect on copper	Deg.corr.	1	DIN 51 811
Resistance to oxidation			
100 h with Cu – Fe catalyst	hPa	<400	DIN 51 508
Flow pressure –30°C	hPa	<500	DIN 51 806

AGNINDO
ARTHA SENTOSA

PT. AGNINDO ARTHA SENTOSA

📍 Sales & Marketing Office :

Jl. Gunung Sahari Raya No. 51.2
Jakarta 10610, Indonesia

☎ +6221 420 9033

🌐 www.agnindo.co.id

✉ info@agnindo.co.id



Fire
Detection



Fire
Protection



Industrial
Lubricants



HVAC

Authorized distributor of Fuchs products in Indonesia

Sales : ✉ sales@agnindo.co.id

Marketing : ✉ marketing@agnindo.co.id

MarCom : ✉ marcom@agnindo.co.id

Whilst the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.