

Product - I N F O R M A T I O N



RENOLIT HV-TAC 2

Lithium complex EP grease

Description

RENOLIT HV-TAC 2 is a multi-purpose grease, contains extreme pressure, anti-wear, anti-oxidation and corrosion preventive additive.

It has good EP properties and protects against corrosion. It is high shear stable product suitable for long-term lubrication. It can be used for a wide temperature range, up to 180°C for short periods.

Benefits

- Excellent corrosion protection
- Good mechanical stability
- High temperature application

Application

- RENOLIT HV-TAC 2 is widely used on the points, such as heavy loaded bearings, vehicles, wheel bearings, semi-trailer axles, chassis and etc. It is also recommended to the different condition, which need lubricating.

Storage

Prerequisites are the correct storage in unopened, original containers, protection from direct sunlight and rain and a storage temperature of up to + 40°C.

After the containers have been opened, adequate precautions must be taken to prevent the ingress of dust, dirt, water, etc. and the contents should be consumed as rapidly as possible.

Package

180kg

While the information and figures given here are typical of current production and confirm to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

Product - I N F O R M A T I O N



RENOLIT HV-TAC 2

Typical Data

Properties	Unit	Data	Test Method
Color		Red	
Thickener		Lithium complex soap	
Dropping point	°C	> 250	ASTM D 566
NLGI grade		2	DIN 51 818
Worked penetration	0.1mm	265 – 295	ASTM D 217
Base oil viscosity at, 40°C	mm ² /s	460	ASTM D 445
Four ball weld load	N	> 3000	ASTM D 2596
Temperature range short term	°C	-20 ~ 150 200	
DIN classification		KP 2 P-20	DIN 51502
ISO classification		L-X-BEEB 2	ISO 6743-9

AGNINDO
ARTHA SENTOSA

PT. AGNINDO ARTHA SENTOSA

📍 Sales & Marketing Office :
Jl. Gunung Sahari Raya No. 51.2
Jakarta 10610, Indonesia

☎ +6221 420 9033
🌐 www.agnindo.co.id
✉ info@agnindo.co.id

Authorized distributor of Fuchs products in Indonesia



Fire
Detection



Fire
Protection



Industrial
Lubricants



HVAC

Sales : ✉ sales@agnindo.co.id

Marketing : ✉ marketing@agnindo.co.id

MarCom : ✉ marcom@agnindo.co.id

While the information and figures given here are typical of current production and confirm to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products.

FUCHS INDONESIA

Modification on 13/02/08

PI-RT-HV TAC.2